



RACK CONVEYOR DISHWASHER SRC-2200

85/126 baskets per hour (up to 2.200 plates/hour)



WARE WASHING
RACK CONVEYOR DISHWASHERS



SALES DESCRIPTION

Washing + rinsing.
2 speed.

FEATURES AND BENEFITS

- ✓ Fully stainless steel jacket.
- ✓ Inlet and outlet splash guards are standard.
- ✓ Stainless steel central rack feed system.
- ✓ Process cycles are divided by rubber curtains.
- ✓ Automatic cycle start.

Economy

- ✓ Energy saving rinse supply switch.
- ✓ Pressure controller in the rinse section to limit consumption.
- ✓ Programmed automatic stops if there is no loading.
- ✓ Stop and freezing of timer when the limit switch actuates.

Cleaning and maintenance

- ✓ Wide pivoting door allowing access for cleaning or inspection purpose.
- ✓ Detachable arms and dispersers for easier cleaning.
- ✓ Sloped removable stainless steel filters with independent removable basket.
- ✓ Easy boiler emptying by loosening a hose.
- ✓ Failures are easily detected thanks to the warning lights.
- ✓ Easy to repair without moving the machine.

Washing

- ✓ Stainless steel wash arms and deep-drawn dispersers.
- ✓ Efficient and durable wash arm dispersers.
- ✓ Powerful, self-draining vertical wash pump.
- ✓ Easy to install detergent dispenser intake in washing tank. Rinsing

Rinsing

- ✓ Stainless steel rinse arms and powerful, stainless steel, deep-drawn dispersers.
- ✓ Automatic boiler filling with no failure risk for heating elements.
- ✓ Temperature control with high precision probes.
- ✓ Visualisation and adjustment of washing and rinsing temperatures in the digital display by pressing a button.
- ✓ Easy to install rinse aid dispenser intake in boiler.

INCLUDES

- ✓ Inlet and outlet splash guards are standard.

ACCESSORIES

- | | |
|---|--|
| <input type="checkbox"/> Drying units | <input type="checkbox"/> Single exit tables |
| <input type="checkbox"/> Manual water softeners | <input type="checkbox"/> Roller conveyor and corner roller conveyor |
| <input type="checkbox"/> Automatic water softeners | <input type="checkbox"/> Machined curve |
| <input type="checkbox"/> 500 x 500 mm. baskets | <input type="checkbox"/> CA Extraction hood |
| <input type="checkbox"/> Inserts, supplements & similar | <input type="checkbox"/> EV Extraction hood with motor |
| <input type="checkbox"/> Loading table for corner situation for rack conveyor dishwashers | <input type="checkbox"/> CV Extraction hood with steam condensation |
| <input type="checkbox"/> Central sorting tables | <input type="checkbox"/> Connecting tables for Pass-Through dishwashers and rack conveyors |
| <input type="checkbox"/> Double connection central sorting table | <input type="checkbox"/> Drying unit for corner situation |



sammic | www.sammic.com
Food Service Equipment Manufacturer

Polígono Basarte, 1.
20720 Azkoitia, Spain

phone +34 943 15 72 36
sales@sammic.com



Project

Date

Item

Qty

Approved

product sheet
updated 26/11/2019



RACK CONVEYOR DISHWASHER SRC-2200

85/126 baskets per hour (up to 2.200 plates/hour)



WARE WASHING
RACK CONVEYOR DISHWASHERS

SPECIFICATIONS

Production

- ✓ Production baskets/hour: 85 / 126
- ✓ Production plates/hour: 1530 / 2200

Wash

- ✓ Temperature: 55 °C - 65 °C
- ✓ Wash tank capacity: 100 l
- ✓ Pump: 3 Hp / 2250 W
- ✓ Wash heating element: 9000 W

Rinse

- ✓ Temperature: 80 °C - 90 °C
- ✓ Water consumption: 300 l/h
- ✓ Rinse heating element: 18000 W
- ✓ Boiler capacity: 20 l

Drag

- ✓ Drag motor power: 0.25 Hp / 180 W

Loading

- ✓ Central module total power : 29580 W

External dimensions (WxDxH)

- ✓ Width: 1700 mm
- ✓ Depth: 829 mm
- ✓ Height: 1520 mm

Net weight: 250 Kg

Water Intake: 3/4 "

Drain diameter: 1 1/2 "

Noise level (1m.): 71 dB(A)

Electrical supply:

- ✓ 400V / 50 Hz / 3N
- ✓ 220V / 60 Hz / 3

- ✓ 440V / 60 Hz / 3

Please note: +3kW rinse heating element in models equipped with steam condenser.

sammic | www.sammic.com
Food Service Equipment Manufacturer

Polígono Basarte, 1.
20720 Azkoitia, Spain

phone +34 943 15 72 36
sales@sammic.com



Project

Date

Item

Qty

Approved

product sheet
updated 26/11/2019