



VACUUM SEALER SU-416

Tabletop model. 16 m³/h. 420 mm.



FOOD PRESERVATION AND SOUS-VIDE
VACUUM PACKING MACHINES - "SENSOR ULTRA" LINE



SALES DESCRIPTION

420 mm. sealing bar.

16 m³/h Busch vacuum pump.

Vacuum controlled by sensor.

FEATURES AND BENEFITS

- ✓ Powered by Busch.
- ✓ Vacuum controlled by sensor.
- ✓ Vacuum PLUS.
- ✓ LCD colour screen: all information at a glance.
- ✓ Backlit touch keyboard.
- ✓ Programmable: 25-programme memory. Blocking option.
- ✓ "Pause" button.
- ✓ Phased vacuum programme.
- ✓ Detection of the evaporation of liquids.
- ✓ Double seal.
- ✓ Cordless sealing bar.
- ✓ Progressive decompression.
- ✓ Vac-Norm ready with Automatic decompression.
- ✓ Stainless steel body and chamber. Deep-drawn chamber.
- ✓ Damped transparent lid of high durability polycarbonate.
- ✓ Dry-oil programme for drying the pump.
- ✓ Working hours counter for oil changes.
- ✓ Safety system with protection against vacuum failure.

INCLUDES

- ✓ BUSCH pump.
- ✓ Sensor Controls.
- ✓ 25 programmable settings.
- ✓ Vacuum PLUS: up to 10 seconds of extra vacuum pull.
- ✓ Soft air function.
- ✓ Clear methacrylate lid.
- ✓ "PAUSE" function.
- ✓ Liquid detection system.
- ✓ Dry oil cycle.
- ✓ NSF Approved.
- ✓ Filling plate.

ACCESSORIES

- ☐ Bag cutting kits
- ☐ Filling plates
- ☐ Liquid insert plates
- ☐ Vac-norm external vacuum kits
- ☐ Vac-norm containers
- ☐ Smooth bags for vacuum packing
- ☐ Trolley for vacuum packing machines
- ☐ Thermal labels for CG2 / RB printer
- ☐ RB Desktop printer for SU vacuum packing machines *
- ☐ Thermal transfer labels for RB printer



sammic | www.sammic.com
Food Service Equipment Manufacturer

Polígono Basarte, 1.
20720 Azkoitia, Spain

phone +34 943 15 72 36
sales@sammic.com



Project

Date

Item

Qty

Approved

product sheet
updated 30/04/2020



VACUUM SEALER SU-416

Tabletop model. 16 m³/h. 420 mm.



SPECIFICATIONS

Pump capacity: 16 m³/h

Pump capacity (60 Hz): 19 m³/h

Bar length: 420 mm

Total loading: -- W

Vacuum pressure (maximum): 2 mbar

Internal dimensions

✓ Width: 430 mm

✓ Depth: 415 mm

✓ Height: 180 mm

External dimensions (WxDxH)

✓ Width: 484 mm

✓ Depth: 529 mm

✓ Height: 448 mm (230V) / 529 mm (120V)

Net weight: 50.8 Kg

Noise level (1m.): 75 dB(A)

Background noise: 32 dB(A)

Crated dimensions

600 x 600 x 610 mm

Gross weight: 56.8 Kg.

AVAILABLE MODELS

1140760	Vacuum packing machine SU-416 230/50-60/1
1140761	Vacuum packing machine SU-416G 230/50-60/1
1140762	Vacuum packing machine SU-416P 230/50-60/1
1140763	Vacuum packing machine SU-416GP 230/50-60/1
1140765	Vacuum packing machine SU-416 120/50-60/1
1140766	Vacuum packing machine SU-416G 120/50-60/1
1140767	Vacuum packing machine SU-416P 120/50-60/1
1140768	Vacuum packing machine SU-416GP 120/50-60/1
1140769	Vacuum packing machine SU-416G+ 120/50-60/1
1140770	Vacuum packing machine SU-416GP+ 120/50-60/1

* Ask for special versions availability

 **sammic** | www.sammic.com
Food Service Equipment Manufacturer

Polígono Basarte, 1.
20720 Azkoitia, Spain

phone +34 943 15 72 36
sales@sammic.com



Project

Date

Item

Qty

Approved

FOOD PRESERVATION AND SOUS-VIDE
VACUUM PACKING MACHINES - "SENSOR ULTRA" LINE

product sheet
updated 30/04/2020