



# VACUUM SEALER SU-420

Tabletop model. 20 m<sup>3</sup>/h. 420 mm.



FOOD PRESERVATION AND SOUS-VIDE  
VACUUM PACKING MACHINES - "SENSOR ULTRA" LINE



## SALES DESCRIPTION

- 420 mm. sealing bar.
- 20 m<sup>3</sup>/h Busch vacuum pump.
- Vacuum controlled by sensor.

## FEATURES AND BENEFITS

- ✓ Powered by Busch.
- ✓ Vacuum controlled by sensor.
- ✓ Vacuum PLUS.
- ✓ LCD colour screen: all information at a glance.
- ✓ Backlit touch keyboard.
- ✓ Programmable: 25-programme memory. Blocking option.
- ✓ "Pause" button.
- ✓ Phased vacuum programme.
- ✓ Detection of the evaporation of liquids.
- ✓ Double seal.
- ✓ Cordless sealing bar.
- ✓ Progressive decompression.
- ✓ Vac-Norm ready with Automatic decompression.
- ✓ Stainless steel body and chamber. Deep-drawn chamber.
- ✓ Damped transparent lid of high durability polycarbonate.
- ✓ Dry-oil programme for drying the pump.
- ✓ Working hours counter for oil changes.
- ✓ Safety system with protection against vacuum failure.

## INCLUDES

- ✓ BUSCH pump.
- ✓ Sensor Controls.
- ✓ 25 programmable settings.
- ✓ Vacuum PLUS: up to 10 seconds of extra vacuum pull.
- ✓ Soft air function.
- ✓ Clear methacrylate lid.
- ✓ "PAUSE" function.
- ✓ Liquid detection system.
- ✓ Dry oil cycle.
- ✓ NSF Approved.
- ✓ Filling plate.

## ACCESSORIES

- ☐ Bag cutting kits
- ☐ Filling plates
- ☐ Liquid insert plates
- ☐ Vac-norm external vacuum kits
- ☐ Vac-norm containers
- ☐ Smooth bags for vacuum packing
- ☐ Trolley for vacuum packing machines
- ☐ Thermal labels for CG2 / RB printer
- ☐ RB Desktop printer for SU vacuum packing machines \*
- ☐ Thermal transfer labels for RB printer



**sammic** | [www.sammic.com](http://www.sammic.com)  
Food Service Equipment Manufacturer

Polígono Basarte, 1. phone +34 943 15 72 36  
20720 Azkoitia, Spain [sales@sammic.com](mailto:sales@sammic.com)



Project	Date
Item	Qty
Approved	

product sheet  
updated 30/04/2020



## VACUUM SEALER SU-420

Tabletop model. 20 m<sup>3</sup>/h. 420 mm.



### SPECIFICATIONS

Pump capacity: 20 m<sup>3</sup>/h

Pump capacity (60 Hz): 24 m<sup>3</sup>/h

Bar length: 420 mm

Total loading: 750 W

Vacuum pressure (maximum): 2 mbar

#### Internal dimensions

✓ Width: 430 mm

✓ Depth: 415 mm

✓ Height: 180 mm

#### External dimensions (WxDxH)

✓ Width: 484 mm

✓ Depth: 529 mm

✓ Height: 448 mm (230V) / 529 mm (120V)

Net weight: 56.7 Kg

Noise level (1m.): 75 dB(A)

Background noise: 32 dB(A)

#### Crated dimensions

600 x 600 x 610 mm

Gross weight: 62.7 Kg.

### AVAILABLE MODELS

1140772	Vacuum packing machine SU-420 230/50-60/1
1140773	Vacuum packing machine SU-420G 230/50-60/1
1140774	Vacuum packing machine SU-420P 230/50-60/1
1140775	Vacuum packing machine SU-420+ 230/50-60/1
1140776	Vacuum packing machine SU-420P+ 230/50-60/1
1140777	Vacuum packing machine SU-420GP 230/50-60/1
1140778	Vacuum packing machine SU-420G+ 230/50-60/1
1140779	Vacuum packing machine SU-420GP+ 230/50-60/1
1140781	Vacuum packing machine SU-420 120/50-60/1
1140782	Vacuum packing machine SU-420G 120/50-60/1
1140783	Vacuum packing machine SU-420P 120/50-60/1
1140784	Vacuum packing machine SU-420+ 120/50-60/1
1140785	Vacuum packing machine SU-420P+ 120/50-60/1 (with PLUS welding option)
1140786	Vacuum packing machine SU-420GP 120/50-60/1
1140787	Vacuum packing machine SU-420G+ 120/50-60/1
1140788	Vacuum packing machine SU-420GP+ 120/50-60/1

\* Ask for special versions availability

 **sammic** | [www.sammic.com](http://www.sammic.com)

**Food Service Equipment Manufacturer**

Polígono Basarte, 1.  
20720 Azkoitia, Spain

phone +34 943 15 72 36  
[sales@sammic.com](mailto:sales@sammic.com)



Project

Date

Item

Qty

Approved

product sheet  
updated 30/04/2020

FOOD PRESERVATION AND SOUS-VIDE  
VACUUM PACKING MACHINES - "SENSOR ULTRA" LINE