



VACUUM SEALER SU-520

Tabletop model. 20m³/h. 420+420 mm.



FOOD PRESERVATION AND SOUS-VIDE
VACUUM PACKING MACHINES - "SENSOR ULTRA" LINE



SALES DESCRIPTION

Two sealing bars (420+420 mm.)
20 m³/h Busch vacuum pump.
Vacuum controlled by sensor.

FEATURES AND BENEFITS

- ✓ Powered by Busch.
- ✓ Vacuum controlled by sensor.
- ✓ Vacuum PLUS.
- ✓ LCD colour screen: all information at a glance.
- ✓ Backlit touch keyboard.
- ✓ Programmable: 25-programme memory. Blocking option.
- ✓ "Pause" button.
- ✓ Phased vacuum programme.
- ✓ Detection of the evaporation of liquids.
- ✓ Double seal.
- ✓ Cordless sealing bar.
- ✓ Progressive decompression.
- ✓ Vac-Norm ready with Automatic decompression.
- ✓ Stainless steel body and chamber. Long-shaped chamber.
- ✓ Damped transparent lid of high durability polycarbonate.
- ✓ Dry-oil programme for drying the pump.
- ✓ Working hours counter for oil changes.
- ✓ Safety system with protection against vacuum failure.

INCLUDES

- ✓ BUSCH pump.
- ✓ Sensor Controls.
- ✓ 25 programmable settings.
- ✓ Vacuum PLUS: up to 10 seconds of extra vacuum pull.
- ✓ Soft air function.
- ✓ Clear methacrylate lid.
- ✓ "PAUSE" function.
- ✓ Liquid detection system.
- ✓ Dry oil cycle.
- ✓ NSF Approved.
- ✓ Filling plate.

ACCESSORIES

- ☐ Bag cutting kits
- ☐ Filling plates
- ☐ Liquid insert plates
- ☐ Vac-norm external vacuum kits
- ☐ Vac-norm containers
- ☐ Smooth bags for vacuum packing
- ☐ Trolley for vacuum packing machines
- ☐ Thermal labels for CG2 / RB printer
- ☐ RB Desktop printer for SU vacuum packing machines *
- ☐ Thermal transfer labels for RB printer



sammic | www.sammic.com
Food Service Equipment Manufacturer

Polígono Basarte, 1.
20720 Azkoitia, Spain

phone +34 943 15 72 36
sales@sammic.com



Project

Date

Item

Qty

Approved

product sheet
updated 30/04/2020



VACUUM SEALER SU-520

Tabletop model. 20m³/h. 420+420 mm.



SPECIFICATIONS

Pump capacity: 20 m³/h

Pump capacity (60 Hz): 24 m³/h

Bar length: 420 mm

Total loading: 750 W

Vacuum pressure (maximum): 2 mbar

Internal dimensions

✓ Width: 560 mm

✓ Depth: 430 mm

✓ Height: 183 mm

External dimensions (WxDxH)

✓ Width: 625 mm

✓ Depth: 537 mm

✓ Height: 513 mm (230V) / 594 mm (120V)

Net weight: 81.1 Kg

Noise level (1m.): 75 dB(A)

Background noise: 32 dB(A)

Crated dimensions

604 x 777 x 650 mm

Gross weight: 85 Kg.

AVAILABLE MODELS

1140790	Vacuum packing machine SU-520 230/50-60/1
1140791	Vacuum packing machine SU-520G 230/50-60/1
1140792	Vacuum packing machine SU-520P 230/50-60/1
1140793	Vacuum packing machine SU-520+ 230/50-60/1
1140794	Vacuum packing machine SU-520P+ 230/50-60/1
1140795	Vacuum packing machine SU-520GP 230/50-60/1
1140796	Vacuum packing machine SU-520G+ 230/50-60/1
1140797	Vacuum packing machine SU-520GP+ 230/50-60/1
1140799	Vacuum packing machine SU-520 120/50-60/1
1140800	Vacuum packing machine SU-520G 120/50-60/1
1140801	Vacuum packing machine SU-520P 120/50-60/1
1140802	Vacuum packing machine SU-520+ 120/50-60/1
1140803	Vacuum packing machine SU-520P+ 120/50-60/1
1140804	Vacuum packing machine SU-520GP 120/50-60/1
1140805	Vacuum packing machine SU-520G+ 120/50-60/1
1140806	Vacuum packing machine SU-520GP+ 120/60/1

* Ask for special versions availability

sammic | www.sammic.com

Food Service Equipment Manufacturer

Polígono Basarte, 1.
20720 Azkoitia, Spain

phone +34 943 15 72 36
sales@sammic.com



Project

Date

Item

Qty

Approved

FOOD PRESERVATION AND SOUS-VIDE
VACUUM PACKING MACHINES - "SENSOR ULTRA" LINE

product sheet
updated 30/04/2020